

MATERIAL SAFETY DATA SHEET

Engineered Wood Trim

1 Product Identification

Manufacturer Name and Address:

Collins Products LLC

6410 Highway 66
 Klamath Falls, OR 97601
 Emergency Phone: 541.885.3214
 Phone of Additional Information: 541.885.3303

Product Name: Hardboard

Synonyms(s): None

Prepared By: Environmental, Safety, & Health Services

Date Prepared: 11/99

Date Revised: 4/1/10

MSDS#: CPKF-0005

2 Hazardous Ingredient & Identity Information

Name/CAS#	%	Exposure Limits*
Wood	90-91	OSHA PEL-TWA 5 mg/m ³ (a)
CAS# - None		ACGIH TLV-TWA 5 mg/m ³ (b)
		ACGIH TLV-STEL 10 mg/m ³ (c)
		ACGIH TLV-TWA 1 mg/m ³ (d)
		Other (e)
Resin Solids	5-6	OSHA PEL-TWA 1 ppm (f)
Phenol formaldehyde		OSHA PEL-STEL 2 ppm (f)
CAS# None		ACGIH TLV-TWA 1 ppm (f)
		Other (e)
Wax	2-3	OSHA PEL-TWA None
CAS# 8002-74-2		ACGIH TLV-TWA 2 mg/m ³ (h)
Water based primer	1-2	OSHA PEL-TWA None
or sealer		ACGIH PEL-TWA None
CAS# None		
Top spray –	<1	OSHA PEL-TWA 1 ppm (f)
Melamine		OSHA PEL-STEL 2 ppm (f)
Formaldehyde		
CAS# None		ACGIH TLV-TWA 1 ppm (f)
		OTHER
Laminating adhesive	<.5	OSHA PEL-TWA 1 ppm (g)
Formaldehyde		OSHA PEL-STEL .75 ppm (g)
CAS# 50-00-0		ACGIH TLV-TWA .3 ppm (g)
		OTHER

(a) Alder, aspen, beech, cotton wood, fir, gum hemlock, hickory, maple, oak, pines, poplar, spruce, and/or western red cedar.

(b) Softwood dust 8-hour TWA

(c) Selected hardwoods (oak, beech) 8-hour TWA

(d) Softwood total dust 15 minute STEL

(e) Some states use an 8-hour PEL-TWA of 10.0 mg/m³ for wood Dust. Washington has established an 8-hour PEL-TWA of 5.0 Mg/m³ for non-allergenic and 2.5 mg/m³ for allergenic wood dust.

(f) As free formaldehyde

(g) Washington ceiling for formaldehyde is 1 ppm. Oregon 8-hour PEL-TWA for formaldehyde is 2 ppm.

(h) As paraffin fume wax.

NOTE:

OSHA = Occupational Safety and Health Administration

ACGIH = American Conference of Governmental Industrial Hygienists

PEL = Permissible Exposure Limit

TWA = Time Weighted Average

TLV = Threshold Limit Value

STEL = Short Term Exposure Limit

Appearance and odor:

A ligno cellulosic matrix of interlocking wood fibers (primarily pine, fir, Hemlock, and Douglas fir), having a slight aromatic odor.

3 Physical/Chemical Characteristics

BOILING POINT (1atm):	N/A
VAPOR PRESSURE (mm Hg):	N/A
VAPOR DENSITY (Air=1; 1 atm):	N/A
SPECIFIC GRAVITY (H ₂ O=1):	0.40-0.80
MELTING POINT:	N/A
EVAPORATION RATE (Butyl Acetate=1):	N/A
SOLUBILITY IN WATER % by Weight):	<0.1%
% VOLATILE BY VOLUME:	0

4 Fire and Explosion Hazard Data

FLASH POINT (°F or° C)	N/A
FLAMMABLE LIMITS:	
LEL:	N/A
UEL:	N/A
EXTINGUISHING MEDIA:	Water, carbon dioxide, sand,
AUTOIGNITION TEMPERATURE:	400°F-500°F (204°C-260°C).
SPECIAL FIRE FIGHTING PROCEDURES:	None
UNUSUAL FIRE AND EXPLOSION HAZARDS:	Depending on moisture content, and more importantly, particle diameter, wood dust may explode in the presence of an ignition source. An airborne concentration of 40 grams (40,000 mg) of dust per cubic meter of air is often used as the LEL for wood dusts.

MSDS: Engineered Wood Trim

5 Reactivity Data

Stability:	() Unstable	(x) Stable
Conditions to Avoid:	N/A	
Incompatibility (Material to avoid):	Avoid contact with oxidizing agents. Avoid open flames. This product may ignite at temperatures in excess of 400°F (204°C).	
Hazardous decomposition or by-products:	Thermal decomposition products include carbon monoxide, carbon dioxide, aliphatic aldehydes, rosin acids, terpenes, and polycyclic aromatic hydrocarbons.	
Hazardous Polymerization: Conditions to Avoid:	() May occur	(x) Will Not Occur

6 Precautions for Safe Handling and Use

Steps to be Taken in Case of Material is Released or Spilled:

Not applicable for product in purchased form. Wood dust generated from sawing, sanding, drilling, or routing of this product may be vacuumed or shoveled for recovery or disposal. Avoid dusty conditions and provide good ventilation. Use NIOSH/MSHA approved respirator and goggles where ventilation is not possible.

Waste Disposal Method:

If disposed of or discarded in its purchased form, incineration is preferable. Dry land disposal is acceptable in most states. It is, however, the user's responsibility to determine at the time of disposal whether your product meets RCRA criteria for hazardous waste. Follow applicable federal, state, and local regulations.

Precautions to be Taken in Handling and Storage:

No special handling precaution is required. Keep in a cool dry place away from open flames. This product may release small quantities of gaseous formaldehyde in amounts below the health hazard level (0.10 ppm) determined by OSHA. Store in well ventilated, cool, dry place away from open flame.

Other Precautions

A NIOSH/OSHA approved full-face respirator or half-face respirator with chemical goggles must be worn when the formaldehyde and/or wood dust exposure limits are exceeded. It is recommended that a full-face respirator and half-face respirator have a combination formaldehyde and dust cartridge.

7 Health Hazard Data

Primary Health Hazard:

The primary health hazard posed by this product is thought to be due to exposure to wood dust or free gaseous formaldehyde.

Primary Rout(s) of Exposure:
() Ingestion:
(x) Skin: Dust
(x) Inhalation: Dust

Acute Health Hazards—Signs and Symptoms of Exposure/ Emergency and First Aid Procedures:

INGESTION: Not applicable with normal use.

EYE CONTACT: Wood dust may cause mechanical irritation. Treat dust in eye as foreign object. Flush with water to remove dust particle. Get medical help if irritation persists.

SKIN CONTACT: Wood dust may cause allergic contact dermatitis in sensitized individuals. Wood dust may also mechanically irritate the skin and cause erythema and hives.

SKIN ABSORPTION: Not known to occur with normal use.

INHALATION: Wood dust may cause unpleasant deposit/obstruction in the nasal passages, resulting in dryness of nose, dry cough, and headaches.

Medical Conditions Generally Aggravated by Exposure:

Wood dust may aggravate preexisting respiratory conditions or allergies.

Chronic Health Hazards:

The federal Dept. of Housing and Urban Development (HUD) recognizes phenolic panel products as low emitters of formaldehyde and has exempted them from Testing and Certification Requirements of the Manufactured Home Construction and Safety Standard (24 CFR Part 3280).

Wood dust(s), depending on the species (for example iroko, cocobana), may cause dermatitis on prolonged, repetitive contact, and respiratory sensitization after prolonged exposure to elevated dust levels (for example Western Red Cedar). Wood dust has been alleged to cause nasal/paranasal sinus cancer (certain European hardwoods, oak, and beech).

Carcinogenicity Listing:

- (x) National Toxicology Program: Formaldehyde, Wood Dust
- (x) IARC Monographs: Formaldehyde, Wood Dust
- (x) OSHA Regulated: Formaldehyde

8 Control Measures

Personal Protective Equipment:

RESPIRATORY PROTECTION—Not applicable for product in purchased form. A NIOSH/MSHA approved respirator is recommended when allowable exposure limits may be exceeded.

PROTECTIVE GLOVES—Not required. However, cloth, canvas or leather gloves are recommended to minimize mechanical irritation from handling product.

EYE PROTECTION—Not applicable for product in purchased form. Goggles or safety glasses are recommended when machining this product.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT—Not applicable for product in purchased form. Outer garments may be desirable in extremely dusty areas.

WORK/HYGIENE PRACTICES—Follow good hygienic and house-keeping practices. Clean up areas where dust settles to avoid excessive accumulation of this combustible material. Minimize blowdown or other practices that generate high airborne dust concentrations.

MSDS: Engineered Wood Trim

Ventilation:

LOCAL EXHAUST—Provide local exhaust as needed so that exposure limits are met.

MECHANICAL (GENERAL)—Provide good ventilation in processing and storage areas as needed so that exposure limits are met.

SPECIAL—Self contained breathing apparatus (SCBA) recommended when fire fighting.

OTHER—N/A

9 Transportation Data

DOT Proper Shipping Name: Not Regulated

Hazard Class/Division Number:

ID Number:

Packing Group:

Label/Placard Required:

DOT Hazardous Substance:

10 User's Responsibility

The information contained in this Material Safety Data Sheet is based on the experience of the Environmental, Safety, & Health professionals and comes from sources believed to be accurate or otherwise technically correct. It is the user's responsibility to determine if this information is suitable for their applications and to follow safety precautions as may be necessary. The user has the responsibility to make sure that this sheet is the most up-to-date issue.

11 Additional Information

Definition of Common Terms:

AGCIH = American Conference of Government Industrial Hygienists

C = Ceiling Limit

CAS # = Chemical Abstract System Number

IARC = International Agency for Research on Cancer

MSHA = Mine Safety and Health Administration

N/A = Not Applicable

NIOSH = National Institute of Occupational Safety and Health

NTP = National Toxicology Program

OSHA = Occupational Safety and Health Administration

PEL = Permissible Exposure Limit

STEL = Short Term Exposure Limit

LTV = Threshold Limit Value

TWA = Time Weighted Average

Manufactured by
COLLINS PRODUCTS LLC
6410 HWY 66
Klamath Falls, OR 97601

800.417.3674 • www.CollinsWood.com

