# **MATERIAL SAFETY DATA SHEET - T07D2011**

# 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

**TRADE NAME:** TAMKO Extruded Lumber

**LABEL:** Skirting, Post Sleeve, Oval Baluster, 2x2 Baluster, 2x4 Rail, Handrail, Universal Rail **USE & DESCRIPTION:** Decking and Dock Construction **CHEMICAL FAMILY:** Mixture

### MANUFACTURED BY: EMERGENCY TELEPHONE NUMBERS;

TAMKO Building Products, Inc. P. O. Box 1404 Joplin, MO 64802-1404 General Information: 1-417-624-6644 (8 a.m. - 5 p.m. CST) Chemtrec: 1-800-424-9300 (24 HOURS)

# 2. HAZARDS IDENTIFICATION

### **EMERGENCY OVERVIEW:**

INHALATION OF PRODUCT DUST MAY CAUSE TEMPORARY UPPER RESPIRATORY IRRITATION. MAY CAUSE SKIN IRRITATION. MAY CAUSE EYE IRRITATION. MAY CAUSE HARMFUL EFFECTS IF SWALLOWED. UNDER NORMAL CONDITIONS OF USE, THE PRODUCT IS NOT EXPECTED TO CREATE ANY EMERGENCY HAZARDS.

HMIS Rating:	NFPA Rating:
Health - *1	Health - 1
Flammability - 1	Flammability - 1
Reactivity - 0	Reactivity - 0

### **POTENTIAL HEALTH EFFECTS:**

**Eye Contact:** If dust enters eye, may cause irritation resulting in tearing, stinging, redness or swelling.

**Skin Contact:** Repeated contact may cause skin irritation due to roughness of product. Redness, drying and cracking of the skin (dermatitis) may occur following prolonged and repeated contact. Prolonged or repeated skin contact could result in absorption of hazardous components.

**Ingestion:** Ingestion of this product may cause irritation of the digestive tract followed by vomiting. Avoid aspiration of vomit into the lungs which can cause inflammation or pneumonitis.

**Inhalation:** Exposure to dust can cause irritation of the nose and throat. Use of this product in well-ventilated working conditions is not expected to cause adverse effects.

### Chronic Effect/Carcinogenicity/Special/Toxic:

Can cause cancer.

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS No.	% by Weight	
Wood Dust	NE	<66	
Plastic	NE	<35	
Proprietary Additives	NE	<15	
NF – Not established			

NE = Not established

# 4. FIRST AID MEASURES

**EYE CONTACT:** Immediately flush eyes with plenty of cool water for at least 20 minutes, occasionally lifting the eye lids to ensure thorough rinsing. Get medical attention if irritation persists. **SKIN CONTACT:** Clean any exposed skin with warm soapy water if possible. If not, and a waterless hand cleaner is used, it should be without pumice. Get medical attention if irritation persists or develops.

**INGESTION:** If swallowed, do not induce vomiting. If vomiting occurs, keep head lower than hips to avoid aspiration of vomit into the lungs which can cause inflammation or pneumonitis. Call poison control center or get immediate medical attention.

**INHALATION:** If inhalation of dust remove person to fresh air. Drink water to clear throat or blow nose to clear. If not breathing, give artificial respiration or give oxygen by trained personnel and get immediate medical attention.

**NOTES TO PHYSICIAN:** Treatment should be based on removing the source of irritation with treatment of symptoms as necessary.

# 5. FIRE FIGHTING MEASURES

**EXTINGUISHING MEDIA:** Dry chemical, CO<sup>2</sup>, or foam preferred. Avoid use of straight-stream water.

**SPECIAL FIRE FIGHTING PROCEDURES:** Combustible. Avoid breathing fumes. Firefighters should not enter confined spaces without wearing NIOSH approved positive pressure breathing apparatus (SCBA) with full face mask and full protective equipment.

**UNUSUAL FIRE OR EXPLOSION HAZARDS:** When heated, fumes may burn if ignition source is provided. Burning product will cause thick black smoke.

**SEE SECTION 10 FOR COMBUSTION PRODUCTS** 

# 6. ACCIDENTAL RELEASE MEASURES

**PRECAUTIONS IF MATERIAL IS SPILLED OR RELEASED:** Pick up large pieces. Do not dry sweep dusts or blow with air in confined area.

**WASTE DISPOSAL METHODS:** Dispose in accordance with applicable Federal, State, and Local regulations. Do not burn.

### 7. HANDLING AND STORAGE

**STORAGE TEMPERATURE:** Store away from heat, all ignition sources and open flames in accordance with applicable laws and regulations. **PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:** Follow recommended work practices and use recommended personal protective clothing and equipment. **THIS PRODUCT SHOULD NOT BE HEATED OR BURNED USING A DIRECT FLAME DEVICE.** 

See Section 8 of this MSDS.

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Exposure Limits

Components	CAS No.	OSHA		ACGIH		
Raw Products		TWA	STEL	TWA	STEL	Unit
Wood Dust	NE	15/ 5*	NE	1/0.5**	NE	mg/m <sup>3</sup>
Plastic	NE	15/5*	NE	10/3*	NE	mg/m <sup>3</sup>

NE= Not established

\* Total Nuisance Dust/Respirable Dust

\*\* Hardwood/Softwood

**RESPIRATORY PROTECTION:** Normally not needed in well-ventilated areas. However, if applicable exposure standards are exceeded or can be exceeded, introduce ventilation to remove dust. If increased ventilation is not possible, use a NIOSH/MSHA approved air-purifying respirator. If concentrations are sufficiently high that this respirator is inadequate, or high enough to cause oxygen deficiency, use a positive pressure self-contained breathing apparatus (SCBA). Follow all applicable respirator use, fitting, and training standards and regulations.

**VENTILATION:** Use only with adequate ventilation to maintain exposures below applicable exposure limits.

**EYE PROTECTION:** Safety glasses with side-shields should be used if eye contact is possible. **SKIN:** Should use leather or cotton gloves and long-sleeve cotton shirt if exposure to dust is possible. Should wear footwear with adequate traction to prevent slipping and falling.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

**APPEARANCE AND ODOR:** Colored wood grained planks and railings **ODOR THRESHOLD:** Not Applicable pH: Not Applicable **BOILING POINT:** Not Applicable MELTING POINT/ FREEZING POINT: Not Applicable **INITIAL BOILING POINT AND BOLING RANGE: Not Applicable** FLASH POINT: Not Applicable EVAPORATION RATE (BUTYL ACETATE = 1): Not Applicable FLAMMABILITY (SOLID AND GAS): Not Applicable UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS: Not Applicable VAPOR PRESSURE: Not Applicable VAPOR DENSITY (AIR = 1): Not Applicable SPECIFIC GRAVITY/RELATIVE DENSITY: Variable **SOLUBILITY (IES):** Not Applicable PARTITION COEFFICIENT: N-OCTANOL/WATER: Not Applicable **AUTOIGNITION TEMPERATURE: Not Applicable** 

# 10. STABILITY AND REACTIVITY

### STABILITY: Stable

**CONDITIONS TO AVOID:** Keep from heat, sparks, open flame and other sources of ignition. Avoid contact with strong oxidizing agents. **THIS PRODUCT SHOULD NOT BE HEATED OR BURNED USING A DIRECT FLAME DEVICE.** 

HAZARDOUS REACTION: Polymerization will not occur.

**INCOMPATIBILTY (MATERIALS TO AVOID):** Strong acids or bases, oxidizing agents and selected amines.

**HAZARDOUS COMBUSTION PRODUCTS:** Carbon monoxide, carbon dioxide, ozone, hydrogen sulfide and various hydrocarbons during heating or burning. These combustion products are not expected unless product is heated or burned.

# 11. TOXICOLOGICAL INFORMATION

**EYE** – May cause eye irritation.

**SKIN** – May cause skin irritation.

**INHALATION** – Dust may cause upper respiratory irritation.

**INGESTION** – May cause harmful effects if swallowed.

## THE FOLLOWING COMPONENT DATA IS PROVIDED FOR USER INFORMATION:

### WOOD DUST

**Cancer -** This product contains wood dust. NTP and IARC have classified wood dust as a known human carcinogen. IARC concluded that there was increased risk of adenocarcinomas of the nasal cavities and paranasal sinuses. The physical nature of this product may help limit any inhalation hazard from wood dust during application. However, physical forces such as grinding, and drilling may liberate wood dust.

Acute Effects - Exposure to wood dust can cause irritation of the eyes, nose and throat causing shortness of breath, dryness and soreness of the throat, sneezing, tearing and conjunctivitus. Chronic Effects – In addition to cancer, breathing of wood dust over a period of time can cause damage to the lung tissue and shortness of breath.

# 12. ECOLOGICAL INFORMATION .

Ecotoxicity – No data available Persistence and degradability – No data available Bioaccumulative potential – No data available Mobility in Soil – No data available Other adverse effects (GHG, Ozone) - No data available

# 13. DISPOSAL CONSIDERATIONS

This product has not been regulated as a hazardous waste by the USEPA. Dispose in accordance with Federal, State, and Local regulations.

### 14. TRANSPORT INFORMATION

This product is not regulated as a hazardous material for transport under 49 CFR or for vessel transport under the IMDG Code.

UN number: Not applicable

UN Proper Shipping Name: Not applicable Packing Group, if applicable: Not applicable

Environmental Hazards: Not applicable

Transport in bulk: Not applicable

Special Precautions: Not applicable

# 15. <u>REGULATORY INFORMATION</u>

**TOXIC SUBSTANCES CONTROL ACT (TSCA):** Some components in this product are listed on the TSCA Inventory.

COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION AND LIABILITY ACT (CERCLA): None

SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 (SARA), TITLE III: Section 302 Extremely Hazardous Substances: None Section 311/312 Hazard Categories: Immediate Health; Delayed Health; Fire Hazard Section 313 Reportable Ingredients: None

### California Proposition 65:

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

# 16. OTHER INFORMATION

• Preparation Date: January, 2012

# **Disclaimer of Liability**

The information and recommendations contained herein are to the best of **TAMKO Building Products**, Inc.'s knowledge and belief, accurate and reliable as of the date issued. **TAMKO Building Products**, Inc. does not warrant or guarantee their accuracy or reliability, and **TAMKO Building Products**, Inc. shall not be liable for any loss or damage arising out of the use thereof.

The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy his or herself that they are suitable and complete for the user's particular use.