

# **Material Safety Data Sheet**

# PRODUCT AND COMPANY IDENTIFICATION

**Product Identification** 

Product ID: LLL0302

Product Name: COLORPLUS BOOTHBAY BLUE JH 70-20 TOUCH-UP

Product Use: Paint product. Print date: 23/Oct/2012 23/Oct/2012 **Revision Date:** 

**Company Identification** 

The Valspar Corporation PO Box 1461

Minneapolis, MN 55440

**Manufacturer's Phone:** 1-612-851-7000

24-Hour Medical Emergency

1-888-345-5732

Phone:

# 2. HAZARDS IDENTIFICATION

### **Primary Routes of Exposure:**

Inhalation Ingestion Skin absorption

#### **Eye Contact:**

· May cause eye irritation.

#### **Skin Contact:**

· Causes skin irritation.

# Ingestion:

• Irritation of the mouth, throat, and stomach.

#### Inhalation:

Causes respiratory tract irritation.

# **Target Organ and Other Health Effects:**

- Kidney injury may occur.
- · Causes headache, drowsiness or other effects to the central nervous system.
- Risk of serious damage to the lungs (by inhalation).

# This product contains ingredients that may contribute to the following potential chronic health effects:

- Chronic exposure may cause permanent damage of health.
- Prolonged exposure to respirable crystalline quartz silica may cause delayed chronic injury (silicosis).
- Prolonged exposure over TLV may produce pneumoconiosis.

# Teratogens:

- · May cause birth defects.
- · Contains material that may cause adverse reproductive effects.

#### Carcinogens:

- Possible cancer hazard. Contains material which may cause cancer based on animal data.
- Cancer hazard. Contains material which can cause cancer.

#### 3. COMPOSITION / INFORMATION ON HAZARDOUS INGREDIENTS

Ingredient Name CAS-No.	Approx. Weight %	Chemical Name
PROPYLENE GLYCOL 57-55-6	10 - 15	1,2-Propylene glycol
TITANIUM DIOXIDE 13463-67-7	5 - 10	Titanium dioxide
C.I. PIGMENT BLACK 26 68186-94-7	1 - 5	C.I. Pigment Black 26
SILICA 14808-60-7	1 - 5	QUARTZ (Si02)
CLAY 66402-68-4	.1 - 1	Ceramic materials and wares, chemicals

If this section is blank there are no hazardous components per OSHA guidelines.

#### 4. FIRST AID MEASURES

#### **Eye Contact:**

Get medical attention, if symptoms develop or persist. Immediately flush eye(s) with plenty of water.

#### **Skin Contact:**

Remove contaminated clothing and shoes. Wash off immediately with plenty of water for at least 15 minutes. Get medical attention, if symptoms develop or persist.

# Ingestion:

Rinse mouth with water. Give one or two glasses of water. Only induce vomiting at the instruction of medical personnel. Get medical attention.

#### Inhalation:

Move injured person into fresh air and keep person calm under observation. Get medical attention, if symptoms develop or persist.

# Medical conditions aggravated by exposure:

Any respiratory or skin condition.

# 5. FIRE FIGHTING MEASURES

Flash point (Fahrenheit): 205 Flash point (Celsius): 96

Lower explosive limit (%):

Upper explosive limit (%):

Autoignition temperature:

not determined
not determined

Sensitivity to impact:

Sensitivity to static discharge: Sensitivity to static discharge is not expected.

Hazardous combustion products: See Section 10.

#### Unusual fire and explosion hazards:

None known.

#### Extinguishing media:

Carbon dioxide, dry chemical, foam and/or water fog.

# Fire fighting procedures:

Firefighters should be equipped with self-contained breathing apparatus and turn out gear. Keep containers and surroundings cool with water spray.

#### 6. ACCIDENTAL RELEASE MEASURES

#### Action to be taken if material is released or spilled:

Ventilate the area. Avoid breathing dust or vapor. Use self-containing breathing apparatus or airmask for large spills in a confined area. Wipe, scrape or soak up in an inert material and put in a container for disposal. See section 7, "Handling and Storage", for proper container and storage procedures. Avoid contact with eyes.

# 7. HANDLING AND STORAGE

# Precautions to be taken in handling and storage:

Keep container closed when not in use. Do not freeze. Since emptied containers may contain product residue, follow all label warnings, even after container is emptied. Do not cut, drill, grind, or weld on or near this container.

#### 8. PERSONAL PROTECTIVE EQUIPMENT AND EXPOSURE CONTROLS

### **Personal Protective Equipment**

#### Eye and face protection:

Wear safety glasses or goggles to protect against exposure.

### Skin protection:

Appropriate chemical resistant gloves should be worn.

#### **Other Personel Protection Data:**

Usual industrial work clothes.

#### Respiratory protection:

If exposure cannot be controlled below applicable limits, use the appropriate NIOSH approved respirator such as an air purifying respirator with organic vapor cartridge and dust/mist filter. Consult the respirator manufacturer's literature to ensure that the respirator will provide adequate protection. Read and follow all respirator manufacturer's instructions.

# Ventilation

Use only in well-ventilated areas. Ovens used for curing should contain a fresh air purge to prevent vapours from accumulating and creating a possible explosive mixture. Ensure adequate ventilation, especially in confined areas.

#### **Exposure Guidelines**

#### **OSHA Permissible Exposure Limits (PEL's)**

Ingredient Name CAS-No.	Approx. Weight %	TWA (final)	Ceilings limits (final)	Skin designations
TITANIUM DIOXIDE 13463-67-7	5 - 10	15 mg/m³ TWA dust total		
C.I. PIGMENT BLACK 26 68186-94-7	1 - 5	total	= 5 mg/m³ Ceiling Mn	
SILICA 14808-60-7	1 - 5	(30)/(%SiO2 + 2) mg/m³ TWA, total dust (250)/(%SiO2 + 5) mppcf TWA, respirable fraction (10)/(%SiO2 + 2) mg/m³ TWA, respirable fraction		
CLAY 66402-68-4	.1 - 1	5 mg/m³ TWA Zr		

# **ACGIH Threshold Limit Value (TLV's)**

Ingredient Name CAS-No.	Approx. Weight %	TWA	STEL	Ceiling limits	Skin designations
TITANIUM DIOXIDE 13463-67-7	5 - 10	10 mg/m³ TWA			
C.I. PIGMENT BLACK 26 68186-94-7	1 - 5	0.2 mg/m <sup>3</sup> TWA Mn			
SILICA 14808-60-7	1 - 5	0.025 mg/m³ TWA respirable fraction			
CLAY 66402-68-4	.1 - 1	0.2 mg/m³ TWA Mn 5 mg/m³ TWA Zr	10 mg/m <sup>3</sup> STEL Zr		

# 9. PHYSICAL PROPERTIES

Odor: Normal for this product type.

Physical State: liquid

pH: not determined

Vapor pressure: 24 mmHg @ 77°F (25°C)

Vapor density (air = 1.0): 7.4

Boiling point: 212°F (100°C)
Solubility in water: not determined
Coefficient of water/oil distribution: not determined

Density (lbs per US gallon):

Specific Gravity:

Evaporation rate (butyl acetate = 1.0):

Flash point (Fahrenheit):

Flash point (Celsius):

96

Lower explosive limit (%):

Upper explosive limit (%):

Autoignition temperature:

not determined
not determined

# 10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to Avoid: None known.

Incompatibility: Strong oxidizing agents

Hazardous Polymerization: None anticipated.

Hazardous Decomposition Products: Carbon monoxide and carbon dioxide. Metal oxide fumes.

# 10. STABILITY AND REACTIVITY

Sensitivity to static discharge:

Sensitivity to static discharge is not expected.

# 11. TOXICOLOGICAL INFORMATION

Ingredient Name	Approx.	NIOSH - Selected LD50s and LC50s
CAS-No.	Weight %	
PROPYLENE GLYCOL	10 - 15	= 20000 mg/kg Oral LD50 Rat
57-55-6		= 20800 mg/kg Dermal LD50 Rabbit
TITANIUM DIOXIDE	5 - 10	> 10000 mg/kg Oral LD50 Rat
13463-67-7		
SILICA	1 - 5	= 500 mg/kg Oral LD50 Rat
14808-60-7		

# Mutagens/Teratogens/Carcinogens:

May cause birth defects. Contains material that may cause adverse reproductive effects.

Possible cancer hazard. Contains material which may cause cancer based on animal data. Cancer hazard. Contains material which can cause cancer.

Contains TIO2 which is listed by IARC as a possible human carcinogen (Group 2B) based on animal data. Neither long term animal studies, nor human epidemiology studies of workers exposed to TIO2 provide an adequate basis to conclude TIO2 is carcinogenic. TIO2 is not classified as a carcinogen by NTP, U.S. OSHA, or the U.S. EPA. Contains crystaline silica. The IARC has determined that crystaline silica inhaled in the form of quartz or cristobablite from occupational sources is carcinogenic to humans (group 1). Refer to IARC monograph 68 in conjunction with the use of these materials. Risk of cancer depends on the duration and level of exposure. In coatings products, risk is due primarily to inhalation of sanding dusts or respirable particles in spray mists. The NTP has also determined that crystaline silica is a known human carcinogen in the form of fine, breathable particles. Risk of cancer depends on duration and level of exposure in coatings products, risk is due primarily to inhalation of sanding dust or respirable particles in spray mist.

Ingredient Name CAS-No.	Approx. Weight %	California Prop 65 - Reproductive (Female)	California Prop 65 - Carcinogen
SILICA	1 - 5		Listed. initial date 10/1/88 -
14808-60-7			carcinogen

Ingredient Name	Approx.	IARC Group 1 - Human	IARC Group 2A - Limited	IARC Group 2B -
CAS-No.	Weight %	Evidence	Human Data	Sufficient Animal Data
TITANIUM DIOXIDE	5 - 10			Monograph 47 [1989]
13463-67-7				
SILICA	1 - 5	Monograph 68 [1997]		
14808-60-7				
CLAY	.1 - 1			Monograph 43 [1988]
66402-68-4				

Ingredient Name CAS-No.	Approx. Weight %	NTP Known Carcinogens	NTP Suspect Carcinogens	NTP Evidence of Carcinogenicity
TITANIUM DIOXIDE 13463-67-7	5 - 10			male rat-negative; female rat-negative; male mice-negative; female mice-negative
SILICA 14808-60-7	1 - 5	Known Human Carcinogen		

Ingredient Name CAS-No.	Approx. Weight %	OSHA - Hazard Communication Carcinogens	OSHA - Specifically Regulated Carcinogens	ACGIH Carcinogens
TITANIUM DIOXIDE 13463-67-7	5 - 10	Present		
SILICA 14808-60-7	1 - 5	Present		A2 Suspected Human Carcinogen
CLAY 66402-68-4	.1 - 1	Present		

#### 12. ECOLOGICAL DATA

No information on ecology is available.

# 13. DISPOSAL CONSIDERATIONS

Disposal should be made in accordance with federal, state and local regulations.

# 14. TRANSPORTATION INFORMATION

#### U.S. Department of Transportation

UN ID Number (msds): **NRPAIN** 

Proper Shipping Name: PAINT, NOT REGULATED

# U.S Hazmat and/or International DG shipment exceptions

The supplier may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

# **Reportable Quantity Description:**

#### International Air Transport Association (IATA):

UN ID Number (msds): NRPAİN

Proper Shipping Name: PAINT, NOT REGULATED

# **International Maritime Organization (IMO):**

IMO UN/ID Number (msds): NRPAIN

Proper Shipping Name: PAINT, NOT REGULATED

# 15. REGULATORY INFORMATION

# **U.S. FEDERAL REGULATIONS:**

Ingredient Name	Approx.	SARA 302	SARA 313	CERCLA RQ in lbs.
CAS-No.	Weight %			
C.I. PIGMENT BLACK 26	1 - 5		YES	
68186-94-7				

#### SARA 311/312 Hazard Class:

Acute: yes Chronic: ves Flammability: no Reactivity: no Sudden Pressure: no

# **U.S. STATE REGULATIONS:**

#### Right to Know:

The specific chemical identity of a component may be withheld as a trade secret under 34 Pennsylvania Code, Chapter 317.

#### Pennsylvania Right To Know:

 SILICA
 14808-60-7

 PROPYLENE GLYCOL
 57-55-6

 TITANIUM DIOXIDE
 13463-67-7

 C.I. PIGMENT BLACK 26
 68186-94-7

#### **Additional Non-Hazardous Materials**

PROPRIETARY RESIN Trade Secret
ISOBUTYRIC ACID MONO ESTER 25265-77-4
PROPRIETARY INGREDIENT Trade Secret

#### **California Proposition 65:**

WARNING! This product contains a chemical known in the State of California to cause cancer.

Rule 66 status of product

Not photochemically reactive.

#### **INTERNATIONAL REGULATIONS - Chemical Inventories**

#### **US TSCA Inventory:**

All components of this product are in compliance with U.S. TSCA Chemical Substance Inventory Requirements.

#### **Canada Domestic Substances List:**

All components of this product are listed on the Domestic Substances List.

#### 16. OTHER INFORMATION

**HMIS Codes** 

Health: 2\*
Flammability: 1
Reactivity: 1

PPE: X - See Section 8 for Personal Protective Equipment (PPE).

# **Abbreviations:**

OSHA - Occupational Safety and Health Administration, IARC - International Agency for Research on Cancer, NIOSH - National Institute of Occupational Safety and Health, NTP - National Toxicology Program, ACGIH - American Conference of Governmental Industrial Hygienists, SCAQMD - South Coast Air Quality Management District, TSCA - Toxic Substances Control Act, IATA - International Air Transport Association, IMO - International Maritime Organization, DOT - Department of Transportation, NA - Not applicable, NOT ESTAB - Not established, N.A.V. - Not available, RQ - Reportable quantity, WT - Weight, MG/CU M - Milligrams per cubic meter, G/L - Grams per liter, MM - Millimeters, MPPCF - Millions of particles per cubic foot, PPM - parts per million, PPT - parts per thousand, TCC/PM - Tag closed cup / Pensky-Martens, PB - Lead, PEL - Permissible exposure level, TWA - Time Weighted Average, STEL - Short term exposure limit, C - Celsius, F - Fahrenheit.

#### Disclaimer:

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option. This MSDS contains additional information required by the state of Pennsylvania.

Regulatory Affairs Department 23/Oct/2012

Preparation Information: Prepared By: Print date: Revision Date: 23/Oct/2012