# valspar if it matters, we're on it.®

# **Material Safety Data Sheet**

# 1. PRODUCT AND COMPANY IDENTIFICATION

Product Identification Product ID: Product Name: Product Use: Print date: Revision Date: Company Identification The Valspar Corporation PO Box 1461 Minneapolis, MN 55440	LLD0314 COLORPLUS SANDSTONE BEIGE JH 30-20 TOUCH-UP Paint product. 23/Oct/2012 23/Oct/2012
Manufacturer's Phone:	1-612-851-7000
24-Hour Medical Emergency Phone:	1-888-345-5732

# 2. HAZARDS IDENTIFICATION

**Primary Routes of Exposure:** Inhalation Ingestion Skin absorption

# Eye Contact:

• May cause eye irritation.

# Skin Contact:

• Causes mild skin irritation.

# Ingestion:

None known.

# Inhalation:

• May cause irritation of respiratory tract.

# Target Organ and Other Health Effects:

• Kidney injury may occur.

# This product contains ingredients that may contribute to the following potential chronic health effects:

- Chronic exposure may cause permanent damage of health.
- Prolonged exposure to respirable crystalline quartz silica may cause delayed chronic injury (silicosis).
- Prolonged exposure over TLV may produce pneumoconiosis.

# Carcinogens:

- Possible cancer hazard. Contains material which may cause cancer based on animal data.
- Cancer hazard. Contains material which can cause cancer.

# **3. COMPOSITION / INFORMATION ON HAZARDOUS INGREDIENTS**

Ingredient Name CAS-No.	Approx. Weight %	Chemical Name
TITANIUM DIOXIDE 13463-67-7	15 - 20	Titanium dioxide
PROPYLENE GLYCOL 57-55-6	10 - 15	1,2-Propylene glycol
SILICA 14808-60-7	1 - 5	QUARTZ (Si02)
CLAY 66402-68-4	.1 - 1	Ceramic materials and wares, chemicals

If this section is blank there are no hazardous components per OSHA guidelines.

# 4. FIRST AID MEASURES

# Eye Contact:

Get medical attention, if symptoms develop or persist. Immediately flush eye(s) with plenty of water.

#### Skin Contact:

Wash off with plenty of water.

#### Ingestion:

Get medical attention if symptoms occur

#### Inhalation:

Move to fresh air. Get medical attention, if symptoms develop or persist.

#### Medical conditions aggravated by exposure:

Any respiratory or skin condition.

# 5. FIRE FIGHTING MEASURES

Flash point (Fahrenheit):	205
Flash point (Celsius):	96
Lower explosive limit (%):	not determined
Upper explosive limit (%):	not determined
Autoignition temperature:	not determined
Sensitivity to impact:	no
Sensitivity to static discharge:	Sensitivity to static discharge is not expected.
Hazardous combustion products:	See Section 10.

# Unusual fire and explosion hazards:

None known.

# **Extinguishing media:**

Carbon dioxide, dry chemical, foam and/or water fog.

# Fire fighting procedures:

Firefighters should be equipped with self-contained breathing apparatus and turn out gear. Keep containers and surroundings cool with water spray.

# 6. ACCIDENTAL RELEASE MEASURES

# Action to be taken if material is released or spilled:

Ventilate the area. Avoid breathing dust or vapor. Use self-containing breathing apparatus or airmask for large spills in a confined area. Wipe, scrape or soak up in an inert material and put in a container for disposal. See section 7, "Handling and Storage", for proper container and storage procedures. Avoid contact with eyes.

# 7. HANDLING AND STORAGE

# Precautions to be taken in handling and storage:

Keep container closed when not in use. Do not freeze. Since emptied containers may contain product residue, follow all label warnings, even after container is emptied. Do not cut, drill, grind, or weld on or near this container.

# 8. PERSONAL PROTECTIVE EQUIPMENT AND EXPOSURE CONTROLS

# **Personal Protective Equipment**

#### Eye and face protection:

Wear safety glasses or goggles to protect against exposure.

#### Skin protection:

Appropriate chemical resistant gloves should be worn.

# **Respiratory protection:**

If exposure cannot be controlled below applicable limits, use the appropriate NIOSH approved respirator such as an air purifying respirator with organic vapor cartridge and dust/mist filter. Consult the respirator manufacturer's literature to ensure that the respirator will provide adequate protection. Read and follow all respirator manufacturer's instructions.

# Ventilation

Use only in well-ventilated areas. Ensure adequate ventilation, especially in confined areas.

# **Exposure Guidelines**

# OSHA Permissible Exposure Limits (PEL's)

Ingredient Name CAS-No.	Approx. Weight %	TWA (final)	Ceilings limits (final)	Skin designations
TITANIUM DIOXIDE 13463-67-7	15 - 20	15 mg/m <sup>3</sup> TWA dust total		
SILICA 14808-60-7	1 - 5	(30)/(%SiO2 + 2) mg/m <sup>3</sup> TWA, total dust (250)/(%SiO2 + 5) mppcf TWA, respirable fraction (10)/(%SiO2 + 2) mg/m <sup>3</sup> TWA, respirable fraction		
CLAY 66402-68-4	.1 - 1	5 mg/m³ TWA Zr		

# ACGIH Threshold Limit Value (TLV's)

Ingredient Name CAS-No.	Approx. Weight %	TWA	STEL	Ceiling limits	Skin designations
	15 - 20	10 mg/m <sup>3</sup> TWA			
13463-67-7		_			
SILICA	1 - 5	0.025 mg/m <sup>3</sup> TWA			
14808-60-7		respirable fraction			
CLAY	.1 - 1	0.2 mg/m <sup>3</sup> TWA Mn	10 mg/m <sup>3</sup> STEL Zr		
66402-68-4		5 mg/m <sup>3</sup> TWA Zr			

# 9. PHYSICAL PROPERTIES

Odor: Physical State: pH: Vapor pressure: Vapor density (air = 1.0): Boiling point: Solubility in water: Coefficient of water/oil distribution: Density (lbs per US gallon): Specific Gravity: Evaporation rate (butyl acetate = 1.0): Flash point (Fahrenheit): Flash point (Celsius): Lower explosive limit (%): Upper explosive limit (%):	Normal for this product type. liquid not determined 24 mmHg @ 77°F (25°C) 7.4 212°F (100°C) not determined not determined 10.32 1.24 0.1 205 96 not determined not determined
Upper explosive limit (%):	not determined
Autoignition temperature:	not determined

# **10. STABILITY AND REACTIVITY**

Stability:	Stable under normal conditions.
Conditions to Avoid:	None known.
Incompatibility:	Strong oxidizing agents
Hazardous Polymerization:	None anticipated.
Hazardous Decomposition Products:	Carbon monoxide and carbon dioxide. Metal oxide fumes.

# Sensitivity to static discharge:

Sensitivity to static discharge is not expected.

# **11. TOXICOLOGICAL INFORMATION**

0	Approx. Weight %	NIOSH - Selected LD50s and LC50s
TITANIUM DIOXIDE 13463-67-7	15 - 20	> 10000 mg/kg Oral LD50 Rat
		= 20000 mg/kg Oral LD50 Rat
57-55-6		= 20800 mg/kg Dermal LD50 Rabbit
SILICA 14808-60-7	1 - 5	= 500 mg/kg Oral LD50 Rat

# Mutagens/Teratogens/Carcinogens:

Possible cancer hazard. Contains material which may cause cancer based on animal data. Cancer hazard. Contains material which can cause cancer.

Contains TIO2 which is listed by IARC as a possible human carcinogen (Group 2B) based on animal data. Neither long term animal studies, nor human epidemiology studies of workers exposed to TIO2 provide an adequate basis to conclude TIO2 is carcinogenic. TIO2 is not classified as a carcinogen by NTP, U.S. OSHA, or the U.S. EPA. Contains crystaline silica. The IARC has determined that crystaline silica inhaled in the form of quartz or cristobablite from occupational sources is carcinogenic to humans (group 1). Refer to IARC monograph 68 in conjunction with the use of these materials. Risk of cancer depends on the duration and level of exposure. In coatings products, risk is due primarily to inhalation of sanding dusts or respirable particles in spray mists. The NTP has also determined that crystaline silica is a known human carcinogen in the form of fine, breathable particles. Risk of cancer depends on duration and level of exposure in coatings products, risk is due primarily to inhalation of sanding dusts or respirable particles.

Ingredient Name CAS-No.	Approx. Weight %	California Prop 65 - Reproductive (Female)	California Prop 65 - Carcinogen
SILICA	1 - 5		Listed. initial date 10/1/88 -
14808-60-7			carcinogen

Ingredient Name CAS-No.	Approx. Weight %	IARC Group 1 - Human Evidence	IARC Group 2A - Limited Human Data	IARC Group 2B - Sufficient Animal Data
TITANIUM DIOXIDE 13463-67-7	15 - 20			Monograph 47 [1989]
SILICA 14808-60-7	1 - 5	Monograph 68 [1997]		
CLAY 66402-68-4	.1 - 1			Monograph 43 [1988]

Ingredient Name CAS-No.	Approx. Weight %	NTP Known Carcinogens	NTP Suspect Carcinogens	NTP Evidence of Carcinogenicity
TITANIUM DIOXIDE 13463-67-7	15 - 20			male rat-negative; female rat-negative; male mice-negative; female mice-negative
SILICA 14808-60-7	1 - 5	Known Human Carcinogen		

Ingredient Name CAS-No.	Approx. Weight %	OSHA - Hazard Communication Carcinogens	OSHA - Specifically Regulated Carcinogens	ACGIH Carcinogens
TITANIUM DIOXIDE 13463-67-7	15 - 20	Present		
SILICA 14808-60-7	1 - 5	Present		A2 Suspected Human Carcinogen
CLAY 66402-68-4	.1 - 1	Present		

# 12. ECOLOGICAL DATA

No information on ecology is available.

# 13. DISPOSAL CONSIDERATIONS

Disposal should be made in accordance with federal, state and local regulations.

# 14. TRANSPORTATION INFORMATION

# U.S. Department of Transportation

UN ID Number (msds): NRPAIN

# 14. TRANSPORTATION INFORMATION

Proper Shipping Name: PAINT, NOT REGULATED

# U.S Hazmat and/or International DG shipment exceptions

The supplier may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

# **Reportable Quantity Description:**

# International Air Transport Association (IATA):

UN ID Number (msds): NRPAIN Proper Shipping Name: PAINT, NOT REGULATED

International Maritime Organization (IMO):		
IMO UN/ID Number (msds):	NŘPAIN	
Proper Shipping Name:	PAINT, NOT REGULATED	

# **15. REGULATORY INFORMATION**

# **U.S. FEDERAL REGULATIONS:**

SARA 311/312 Hazard Class:	
Acute:	yes
Chronic:	yes
Flammability:	no
Reactivity:	no
Sudden Pressure:	no

#### **U.S. STATE REGULATIONS:**

#### **Right to Know:**

The specific chemical identity of a component may be withheld as a trade secret under 34 Pennsylvania Code, Chapter 317.

# Pennsylvania Right To Know:

TITANIUM DIOXIDE	13463-67-7
SILICA	14808-60-7
PROPYLENE GLYCOL	57-55-6

#### **Additional Non-Hazardous Materials**

PROPRIETARY INGREDIENT	Trade Secret
ISOBUTYRIC ACID MONO ESTER	25265-77-4
PROPRIETARY RESIN	Trade Secret

#### **California Proposition 65:**

WARNING! This product contains a chemical known in the State of California to cause cancer.

Rule 66 status of product

Not photochemically reactive.

# **INTERNATIONAL REGULATIONS - Chemical Inventories**

#### **US TSCA Inventory:**

All components of this product are in compliance with U.S. TSCA Chemical Substance Inventory Requirements.

# Canada Domestic Substances List:

All components of this product are listed on the Domestic Substances List.

# **16. OTHER INFORMATION**

HMIS Codes	
Health:	1*
Flammability:	1
Reactivity:	1
PPE:	X - See Section 8 for Personal Protective Equipment (PPE).

#### Abbreviations:

OSHA - Occupational Safety and Health Administration, IARC - International Agency for Research on Cancer, NIOSH -National Institute of Occupational Safety and Health, NTP - National Toxicology Program, ACGIH - American Conference of Governmental Industrial Hygienists, SCAQMD - South Coast Air Quality Management District, TSCA -Toxic Substances Control Act, IATA - International Air Transport Association, IMO - International Maritime Organization, DOT - Department of Transportation, NA - Not applicable, NOT ESTAB - Not established, N.A.V. - Not available, RQ -Reportable quantity, WT - Weight, MG/CU M - Milligrams per cubic meter, G/L - Grams per liter, MM - Millimeters, MPPCF - Millions of particles per cubic foot, PPM - parts per million, PPT - parts per thousand, TCC/PM - Tag closed cup / Pensky-Martens, PB - Lead, PEL - Permissible exposure level, TWA - Time Weighted Average, STEL - Short term exposure limit, C - Celsius, F - Fahrenheit.

#### **Disclaimer:**

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option. This MSDS contains additional information required by the state of Pennsylvania.

#### **Preparation Information:**

Prepared By: Print date: Revision Date: Regulatory Affairs Department 23/Oct/2012 23/Oct/2012