

# Safety Data Sheet (SDS)



## TimberStrand<sup>®</sup> LSL RimBoard with Flak Jacket<sup>®</sup> Protection

### 1. Identification

TRADE NAME: TimberStrand<sup>®</sup> LSL RimBoard With Flak Jacket<sup>®</sup> Protection

SYNONYMS: None

PRODUCT USES: Building Materials


CHEMICAL NAME/CLASS: Wood Products

MANUFACTURER'S NAME: Weyerhaeuser  
ADDRESS: 33663 Weyerhaeuser Way S., Federal Way WA 98001-9620  
EMERGENCY PHONE: (800) 424-9300 (CHEMTREC)  
BUSINESS PHONE: (253) 924-3865  
INTERNET ACCESS: See section 16  
REVISED DATE: April 16, 2015


### 2. Hazard(s) Identification

Signal Word: **DANGER**

**NOTE:** This product is not hazardous in the form in which it is shipped by the manufacturer but may become hazardous as the result of downstream activities (e.g. cutting, sanding) which creates small particles resulting in the potential hazards as described below.

Classification	Hazard Statement(s)	Pictogram(s)
HEALTH Carcinogen- Category 1A (H350)*	Wood dust may cause nasopharyngeal cancer and/or cancer of the nasal cavities and paranasal sinuses by inhalation	

## 2. Hazard(s) Identification (cont'd.)

Skin Irritation Category 2  (H315)  Specific Target Organ Toxicity- Single Exposure (STOT) Category-3  (H335)	May cause skin irritation   May cause respiratory irritation	
Eye Irritation Category 2B  (H320)	Causes eye irritation	None
Combustible Dust (OSHA Defined Hazard)	If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air	None

\*Hazard codes (GHS)

**HMIS Rating (Scale 0-4):**    **Health = 2\***    **Fire = 1**    **Physical Hazard = 0**  
**NFPA Rating (Scale 0-4):**    **Health = 1**    **Fire = 1**    **Reactivity = 0**

### Precautionary Statement(s)/Codes (GHS):

#### Prevention Statements:

- P210: Keep away from sparks, flame or other heat sources.
- P243: Take precautionary measures against static discharge.
- P260 and P261: Avoid breathing dust.
- P280: Wear appropriate protective equipment for skin exposure. In case of inadequate ventilation wear an approved respirator suitable for conditions of use.
- P362 and P363: Take off contaminated clothing and wash before reuse.

#### Response Statements:

- P304 and P340: If inhaled and breathing becomes difficult, remove person to fresh air and keep comfortable for breathing.
- P308 and P313: If experiencing respiratory symptoms, following removal to fresh air, call a doctor or other qualified medical professional.
- P313: If skin irritation or rash occurs get medical advice/attention.
- P362: Wash contaminated clothing before reuse.
- P352 and P264: If on skin wash with plenty of soap and water.
- P338 and P351: If in eyes, rinse cautiously for several minutes. Remove contact lenses if present and easy to do so.

#### Disposal:

- P501: Dispose of contents in accordance with Federal, state and local regulations.

**Ingredients of Unknown Acute Toxicity (>1%):** NAP

### 3. Composition/Information on Ingredients

Ingredients	CAS#	Wt %
Wood (wood dust, softwood or hardwood)	None	83-87
Polymeric Diphenylmethane Diisocyanate <sup>1</sup> [C <sub>6</sub> H <sub>3</sub> (NCO)CH <sub>2</sub> ] <sub>n</sub>	9016-87-9	3-5
Fire Retardant Coating	None	1-1.7
Antimony trioxide (Sb <sub>2</sub> O <sub>3</sub> )	1309-64-4	0.5-1
Aluminum Trihydrate 2Al(OH) <sub>3</sub>	21645-51-2	1-1.5

Common names: <sup>1</sup> Polymeric MDI

### 4. First Aid Measures

**Inhalation:** Remove to fresh air if respiratory symptoms are experienced. Seek medical help if persistent irritation, severe coughing, breathing difficulty or other serious symptoms occur.

**Eye Contact:** Treat dust in eye as a foreign object. Flush with water to remove dust particles. Remove contact lenses if present and easy to do so. Avoid touching or rubbing eyes to avoid further irritation or injury. Seek medical help if irritation persists.

**Skin Contact:** Wood dust may elicit contact dermatitis. Seek medical help if rash, irritation or dermatitis persists.

**Skin Absorption:** Not known to be absorbed through the skin.

**Ingestion:** Not applicable under normal use.

**Symptoms or Effects:**

Acute Symptoms/Effects – Wood dust may cause mechanical irritation of the respiratory system. Wood dust can cause physical obstructions in the nasal passages, resulting in dryness of nose, dry cough, and sneezing. Wood dust may cause mechanical irritation of the eyes. Coating particulate containing acidic media may be irritating to the skin, eyes and mucous membranes. Breathing acidic vapors formed at temperatures high enough to cause expansion can be very irritating to the eyes and respiratory system.

Delayed Symptoms/Effects – Unique delayed effects are not anticipated after exposure. See Section 11 for additional information on chronic effects.

### 5. Fire-fighting Measures

**Extinguishing Media and Restrictions:** Water, carbon dioxide and sand.

**Specific Hazards, Anticipated Combustion Products:** Thermal decomposition can release carbon monoxide, oxides of nitrogen, carbon dioxide, sulfuric acid vapors and/or sulfur gases including SO<sub>2</sub>, hydrogen chloride, hydrogen bromide and polycyclic aromatic hydrocarbons. Natural decomposition of organic materials such as wood may produce toxic gases and an oxygen deficient atmosphere in enclosed or poorly ventilated areas.

**Autoignition Temperature:** Variable [typically 400°-500°F (204°-260°C)]

**Special Firefighting Equipment/Procedures:** Heat from a fire will release a significant volume of acid vapors. Wear NIOSH-approved self contained breathing apparatus and appropriate protective clothing for the situation.

**Unusual Fire and Explosion Hazards:** Depending on moisture content and more importantly, particle diameter and airborne concentration, wood and resin dust may explode in the presence of an ignition source. Wood and resin dust may similarly deflagrate (combustion without detonation like an explosion) if ignited in an open or loosely contained area. An airborne concentration of 40 grams (40,000 mg) of dust per cubic meter of air is often used as the LEL for wood dusts. Reference NFPA Standards 654, 664 and the NFPA *Fire Protection Handbook* for guidance. Ventilation systems should be kept clean and precautions should be taken to prevent sparks or other ignition sources.

## 6. Accidental Release Measures

**Steps to be taken in case Material Is Released or Spilled:** Sweep or vacuum up for recovery and disposal. Avoid creating dusty conditions whenever feasible. Maintain good housekeeping to avoid accumulation of wood and resin dust on exposed surfaces. Use approved filtering facepiece respirator (“dust mask”) or higher levels of respiratory protection as indicated and goggles where ventilation is not possible and exposure limits may be exceeded or for additional worker comfort.

## 7. Handling and Storage

**Precautions to be taken in Handling and Storage:** Dried product dust may pose a combustible dust hazard. Keep away from ignition sources. Avoid eye contact. Avoid prolonged or repeated contact with skin. Avoid prolonged or repeated breathing of wood dust. Store in well-ventilated, cool, dry place away from open flame.

## 8. Exposure Control Measures/Personal Protection

### Exposure Limits/Guidelines:

Ingredient(s)	Agency	Exposure Limit(s)	Comments
Wood (wood dust, softwood and hardwood)	OSHA	PEL-TWA 15 mg/m <sup>3</sup> (see footnote <sup>A</sup> below)	Total dust (PNOR)
	OSHA	PEL-TWA 5 mg/m <sup>3</sup> (see footnote <sup>A</sup> below)	Respirable dust fraction (PNOR)
	ACGIH	TLV-TWA 1 mg/m <sup>3</sup>	Inhalable fraction
Fire Retardant Coatings <sup>1</sup>	OSHA	PEL-TWA 15 mg/m <sup>3</sup> (PNOR)	Total particulate
	OSHA	PEL-TWA 5 mg/m <sup>3</sup> (PNOR)	Respirable fraction
	ACGIH	TLV-TWA 10 mg/ m <sup>3</sup> (PNOS)	Inhalable
	ACGIH	TLV-TWA 3 mg/ m <sup>3</sup> (PNOS)	Respirable
Aluminum Trihydrate	OSHA	PEL-TWA 15 mg/m <sup>3</sup> (PNOR)	Total particulate
	OSHA	PEL-TWA 5 mg/m <sup>3</sup> (PNOR)	Respirable fraction
	ACGIH	TLV-TWA 10 mg/ m <sup>3</sup> (PNOS)	Inhalable
	ACGIH	TLV-TWA 3 mg/ m <sup>3</sup> (PNOS)	Respirable
Antimony Trioxide <sup>B</sup>	OSHA	PEL-TWA 0.5 mg/m <sup>3</sup>	Total dust
	ACGIH	TLV-TWA 0.5 mg/m <sup>3</sup>	Total dust
Polymeric Diphenylmethane Diisocyanate <sup>C</sup>	OSHA ACGIH	None None	

<sup>A</sup> In *AFL-CIO v OSHA*, 965 F. 2d 962 (11th Cir. 1992), the Court overturned OSHA's 1989 Air Contaminants Rule, including the specific PEL's for wood dust that OSHA had established at that time. The 1989 vacated PEL's were: 5 mg/m<sup>3</sup> PEL-TWA and 10 mg/m<sup>3</sup> STEL (15 min), all softwood and hardwood except Western Red Cedar. Wood dust is now regulated by OSHA as “Particulates Not Otherwise Regulated” (PNOR), which is also referred to as “nuisance dust”. However, some states have regulated wood dust PEL's in their state plans. Additionally, OSHA indicated that it may cite employers under the OSH Act general duty clause in appropriate circumstances.

## 8. Exposure Control Measures/Personal Protection (cont'd.)

<sup>B</sup> This ingredient also contains trace amounts of lead and arsenic. Exposures should be controlled to levels as low as reasonably possible.

<sup>C</sup> This ingredient is the polymerized form of MDI resin.

<sup>1</sup> These ingredients are considered proprietary.

### Ventilation:

**LOCAL EXHAUST** – Provide local exhaust as needed so that exposure limits are met. Ventilation to control dust should be considered where potential explosive concentrations and ignition sources are present. The design and operation of any exhaust system should consider the possibility of explosive concentrations of wood dust within the system. See “SPECIAL” section below. Use of tool mounted exhaust systems should also be considered, especially when working in enclosed areas.

**MECHANICAL (GENERAL)** – Provide general ventilation in processing and storage areas so that exposure limits are met.

**SPECIAL** – Ensure that exhaust ventilation and material transport systems involved in handling this product contain explosion relief vents or suppression systems designed and operated in accordance with applicable standards if the operating conditions justify their use.

**OTHER ENGINEERING CONTROLS** – Cutting and machining of product should preferably be done outdoors or with adequate ventilation and containment.

### Personal Protective Equipment:

**RESPIRATORY PROTECTION** – Use filtering face piece respirator (“dust mask”) tested and approved under appropriate government standards such as NIOSH (US), CSA (Canada), CEN (EU), or JIS (Japan) where ventilation is not possible and exposure limits may be exceeded or for additional worker comfort or symptom relief. Use respiratory protection in accordance with jurisdictional regulatory requirements similar to the OSHA respiratory protection standard 29CFR 1910.134 following a determination of risk from potential exposures.

**EYE PROTECTION** – Approved goggles or tight fitting safety glasses are recommended when excessive exposures to dust may occur (e.g. during clean up) and when eye irritation may occur.

**PROTECTIVE GLOVES** – Cloth, canvas, or leather gloves are recommended to minimize potential slivers or mechanical irritation from handling product.

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT** – Outer garments which cover the arms may be desirable in extremely dusty areas.

**WORK/HYGIENE PRACTICES** – Follow good hygienic and housekeeping practices. Clean up areas where wood and resin dust settles to avoid excessive accumulation of this combustible material. Minimize compressed air blowdown or other practices that generate high airborne-dust concentrations.

## 9. Physical/Chemical Properties

**Appearance:** TimberStrand<sup>®</sup> LSL RimBoard with Flak Jacket<sup>®</sup> Protection consists of layers of laminated solid wood which are glued together with a polymerized methylene bisphenyl diisocyanate (MDI) resin coated with a pigmented and fire resistant coating. The coating expands when exposed to heat, protecting the wood component from fire and slowing the propagation of flame along the surface of the coated RimBoard. The product has a slightly aromatic/wood odor. The wood component consists of hardwoods.

<b>Odor/ Odor Threshold(s):</b>	NAV
<b>pH:</b>	NAP
<b>Melting/Freezing Point:</b>	NAP
<b>Boiling Point (@ 760 mm Hg) and Range:</b>	NAP
<b>Flash Point:</b>	NAP
<b>Evaporation Rate:</b>	0
<b>Flammability:</b>	NAP

## 9. Physical/Chemical Properties (cont'd.)

<b>Lower / Upper Explosive Limits:</b>	40,000 mg of dust per cubic meter of air is often used as the LEL for wood dusts.
<b>Vapor Pressure (mm Hg):</b>	NAP
<b>Vapor Density (air = 1; 1 atm):</b>	NAP
<b>Relative Density:</b>	NAP
<b>Solubility:</b>	<0.1
<b>Partition Coefficient (n-octonal/water):</b>	NAP
<b>Autoignition Temperature:</b>	Variable [typically 400°-500°F (204°-260°C)]
<b>Decomposition Temperature:</b>	NAV
<b>Viscosity:</b>	NAP
<b>Other Properties:</b>	NAP

## 10. Stability and Reactivity

**Reactivity:** NAP

**Hazardous Polymerization:**  May occur  Will not occur

**Stability:**  Unstable  Stable

**Conditions to Avoid:** Avoid open flame. Product may ignite at temperatures in excess of 400°F (204°C).

**Incompatibility (Materials to Avoid):** Avoid contact with oxidizing agents and drying oils.

**Hazardous Decomposition or By-Products:** Thermal decomposition can release carbon monoxide, oxides of nitrogen, carbon dioxide, sulfuric acid vapors and/or sulfur gases including SO<sub>2</sub>, hydrogen chloride, hydrogen bromide and polycyclic aromatic hydrocarbons. Natural decomposition of organic materials such as wood may produce toxic gases and an oxygen deficient atmosphere in enclosed or poorly ventilated areas.

**Sensitivity to Static Discharge:** Airborne wood dust may be ignited by a static discharge depending on airborne concentrations, particle size and moisture content.

## 11. Toxicological Information

**Likely Route(s) of Exposure:**

- Ingestion:
- Skin: Dust
- Inhalation: Dust
- Eye: Dust

**Signs and Symptoms of Exposure:**

**Wood Dust - NTP:** According to its Report on Carcinogens, Thirteenth Edition, NTP states, "Wood dust is known to be a human carcinogen based on sufficient evidence of carcinogenicity from studies in humans". An association between wood dust exposure and cancer of the nasal cavity has been observed in many case reports, cohort studies, and case-control studies that specifically addressed nasal cancer. Associations with cancer of the nasal cavities and paranasal sinuses were observed both in studies of people whose occupations are associated with wood dust exposure and in studies that directly estimated wood dust exposure. This classification is based primarily on increased risk in the occurrence of adenocarcinomas of the nasal cavities and paranasal sinuses associated with exposure to wood dust. The evaluation did not find sufficient evidence to associate cancers of the oropharynx, hypopharynx, lung, lymphatic and hematopoietic systems, stomach, colon or rectum with exposure to wood dust. There is inadequate evidence for the carcinogenicity of wood dust from studies in experimental animals according to NTP.

## 11. Toxicological Information (cont'd.)

**Wood Dust: IARC – Group 1:** Carcinogenic to humans; sufficient evidence of carcinogenicity. This classification is primarily based on studies showing an association between occupational exposure to wood dust and adenocarcinoma to the nasal cavities and paranasal sinuses. IARC did not find sufficient evidence of an association between occupational exposure to wood dust and cancers of the oropharynx, hypopharynx, lung, lymphatic and hematopoietic systems, stomach, colon or rectum.

### Carcinogenicity Listing(s):

- NTP: Wood dust, Known Human Carcinogen. Crystalline Quartz- Known to be a Human Carcinogen.
- IARC Monographs: Wood dust, Group 1 - carcinogenic to humans. Crystalline Quartz, Group 1- carcinogenic to humans. Antimony trioxide-Group 2B, Possibly Carcinogenic to Humans.
- OSHA Regulated: Not listed

**Toxicity Data:** No specific information available for product in purchased form. Individual component information is listed below.

### Components:

#### Wood dust (softwood or hardwood)

Wood dust generated from sawing, sanding or machining the product may cause respiratory irritation, nasal dryness and irritation, coughing and sinusitis. NTP and IARC (Group 1) classify wood dust as a human carcinogen. See Section 2 above.

#### Crystalline quartz

Oral (acute) Rat: LD<sub>50</sub> = 1,064 mg/kg Dermal (acute). Inhalation (acute): Rat: LC<sub>50</sub>: >2.88 mg/l 4h.  
IARC and NTP: Known Human Carcinogen, see section 3 above.

#### Aluminum trihydrate

Oral (acute) Rat: LD<sub>50</sub> = >5,000 mg/kg

#### Antimony trioxide

Oral (acute) Rat: LD<sub>50</sub> = >34,000 mg/kg

**Target Organs:** Eyes, skin, and respiratory system.

**Note:** Weyerhaeuser evaluated the studies referenced in the ACGIH® TLV® Documentation for Wood Dust and others which included potential allergenic references for wood species which may cause skin or respiratory sensitization. There are a limited number of studies of highly variable consistency which reference sensitization from some species of wood. When the total weight of evidence is considered this product is considered to be an eye, skin and repository irritant and not a respiratory or skin sensitizer according to health hazard classification criteria.

## 12. Ecological Information

**Environmental Toxicity:** NAP for finished product.

Component:

Antimony trioxide: 96 hr LC<sub>50</sub> fish >1,000 mg/l

**Biopersistence and Degradability:** The wood and resin portions of this product would be expected to be biodegradable.

### Polymeric MDI

The effects from a simulated accidental pollution event in a pond with polymeric MDI on different trophic levels of the aquatic ecosystem were investigated (Heimbach F. et.al., 1996). Neither monomeric MDI nor its potential reaction product MDA (4, 4'-diphenylmethanediamine) was detected in water or accumulated by fish. The MDI polymerized to inert polyurea on the sediment of the test ponds. This polymerization formed carbon dioxide, released as bubbles which floated to the water surface. There was no direct effect on the pelagic community (phytoplankton, zooplankton, fish, and macrophytes) of the test ponds. The atmospheric concentration of MDI arising from a release is naturally low on account of MDI's very low volatility.

## 12. Ecological Information (cont'd.)

It is expected that airborne MDI will have a rather short half-life as a consequence of ready degradation to inorganic compounds by hydroxyl radicals present in the troposphere.

### Coating material

May contain residual surface acid that will cause lowering of pH. The acidic nature of the material warrants that it should not be allowed to enter the natural environment.

**Bioaccumulation:** NAV

**Soil Mobility:** NAV

**Other adverse effects:** NAP

## 13. Disposal Considerations

**Waste Disposal Method: CAUTION:** Appreciable levels of sulfuric acid vapors and/or sulfur gases including SO<sub>2</sub> may be emitted if the coating layer is burned in an open fire. Collect and store unused portions and residue for proper disposal as it is the user's responsibility to determine at the time of disposal whether your waste meets RCRA criteria for hazardous waste. Follow applicable federal, state, and local regulations.

## 14. Transport Information

**Mode:** (air, land, water) Not regulated as a hazardous material by the U.S. Department of Transportation. Not listed as a hazardous material in Canadian Transportation of Dangerous Goods (TDG) regulations. Not regulated as a hazardous material by IMDG or IATA regulations concerning the transport of hazardous materials.

<b>UN Proper Shipping Name:</b>	NAP
<b>UN/NA ID Number:</b>	NAP
<b>Hazard Class:</b>	NAP
<b>Packing Group:</b>	NAP
<b>Environmental Hazards (Marine Pollutant):</b>	NAP
<b>Special precautions:</b>	NAP

## 15. Regulatory Information

**TSCA:** All components of this product are listed on the TSCA inventory.

**CERCLA:** NAP

**DSL:** All components of this product are listed on the Canada DSL.

**OSHA:** Wood products are not hazardous under the criteria of the federal OSHA Hazard Communication Standard 29 CFR 1910.1200. However, wood dust as well as antimony trioxide generated by sawing, sanding or machining this product may be hazardous.

### **STATE RIGHT-TO-KNOW:**

California Proposition 65 – **Warning:** Drilling, sawing, sanding or machining wood products generates wood dust, a substance known to the State of California to cause cancer. This product also contains small amounts of chemicals known to the State of California to cause cancer [crystalline silica (airborne unbound particles of respirable size), antimony trioxide and arsenic]. This material also may contain trace amounts of lead which is known to the State of California to cause birth defects and other reproductive harm.



## 15. Regulatory Information (cont'd.)

**NOTE:** However, these chemicals are not anticipated to be potentially released unless the mixture is dried and the end product is cut, ground and/or sanded. The user should determine whether emissions resulting from its site specific use, handling, ventilation design, capacity and final construction design for this product could exceed the safe harbor levels. California's listing was based on the IARC Group 2B classification of antimony trioxide which included studies that showed lung cancer in experimental animals. Relevant human exposures have not shown an association between antimony trioxide/titanium dioxide exposures and cancer.

**Pennsylvania** – When drilling, sawing, sanding or machining, the product may emit wood dust.

Crystalline silica, wood dust, lead, antimony trioxide and paraffin wax appear on Pennsylvania's Appendix A, Hazardous Substance Lists.

**New Jersey** – When cut or otherwise machined, the product may emit wood dust. Wood dust, lead, crystalline silica, antimony trioxide, arsenic and paraffin wax appear on the New Jersey Environmental Hazardous Substance List.

**SARA 313 Information:** This product does not contain any chemical ingredient (s) with known CAS numbers that exceed the de minimis reporting levels established by SARA Title III, section 313 and 40 CFR section 372.

**SARA 311/312 Hazard Category:** This product has been reviewed according to the EPA "Hazard Categories" promulgated under SARA Title III Sections 311 and 312 and is considered, under applicable definitions, to meet the following categories:

An immediate (acute) health hazard	Yes
A delayed (chronic) health hazard	Yes
A corrosive hazard	No
A fire hazard	No
A reactivity hazard	No
A sudden release hazard	No

**FDA:** Not intended for use as a food additive or indirect food contact item.

**WHMIS Classification:** Wood and products made from wood are exempt from WHMIS per the Hazardous Products Act. However, wood dust is considered to be a controlled product: D2A (wood dust, IARC Group 1). Antimony trioxide: D2A very toxic material causing other toxic effects.

## 16. Other Information

**Date Prepared:** 08/30/2012

**Date Revised:** 04/16/2015

**Prepared By:** Weyerhaeuser Company Environment, Health, and Safety.

**Weyerhaeuser SDS available on:**

<http://www.weyerhaeuser.com/Sustainability/Customers/ProductStewardship/SafetyDataSheets>

**User's Responsibility:** The information contained in this Safety Data Sheet is based on the experience of occupational health and safety professionals and comes from sources believed to be accurate or otherwise technically correct. It is the user's responsibility to determine if the product is suitable for its proposed application(s) and to follow necessary safety precautions. The user has the responsibility to ensure that the most current SDS is used.

### Definition of Terms

ACGIH <sup>®</sup>	= American Conference of Governmental Industrial Hygienists
C	= Ceiling Limit
CAS#	= Chemical Abstracts System Number
DOT	= U. S. Department of Transportation
DSL	= Domestic Substance List
EC#	= Identifying Number Assigned to Chemicals Contained in the European Inventory of Existing Chemical Substances (EINECS)
EC <sub>50</sub>	= Effective Concentration That Inhibits the Endpoint to 50% of Control Population

## 16. Other Information (cont'd.)

EPA	=	U.S. Environmental Protection Agency
GHS	=	Globally Harmonized System of Classification and Labelling of Chemicals
HMIS	=	(Canada) Hazardous Materials Identification System
IARC	=	International Agency for Research on Cancer
IATA	=	International Air Transport Association
IMDG	=	International Maritime Dangerous Goods
LC <sub>50</sub>	=	Concentration in Air Resulting in Death To 50% of Experimental Animals
LCLo	=	Lowest Concentration in Air Resulting in Death
LD <sub>50</sub>	=	Administered Dose Resulting in Death to 50% of Experimental Animals
LDLo	=	Lowest Dose Resulting in Death
LEL	=	Lower Explosive Limit
LFL	=	Lower Flammable Limit
MSHA	=	Mine Safety and Health Administration
NAP	=	Not Applicable
NAV	=	Not Available
NIOSH	=	National Institute for Occupational Safety and Health
NFPA	=	National Fire Protection Association
NPRI	=	(Canada) National Pollution Release Inventory
NTP	=	National Toxicology Program
OSHA	=	Occupational Safety and Health Administration
PEL	=	Permissible Exposure Limit
PNOR	=	Particulate Not Otherwise Regulated
PNOS	=	Particulate Not Otherwise Specified
RCRA	=	Resource Conservation and Recovery Act
STEL	=	Short-Term Exposure Limit (15 minutes)
STP	=	Standard Temperature and Pressure
TCLo	=	Lowest Concentration in Air Resulting in a Toxic Effect
TDG	=	(Canada) Transportation of Dangerous Goods
TDLo	=	Lowest Dose Resulting In a Toxic Effect
TLV	=	Threshold Limit Value
TSCA	=	Toxic Substance Control Act
TWA	=	Time-Weighted Average (8 hours)
UFL	=	Upper Flammable Limit
WHMIS	=	(Canada) Workplace Hazardous Materials Information System

# TimberStrand<sup>®</sup> LSL Rimboard with Flak Jacket<sup>®</sup> Protection



## Danger

**Wood dust may cause nasopharyngeal cancer and/or cancer of the nasal cavities and paranasal sinuses by inhalation. May cause respiratory, skin and eye irritation.**

**May form combustible dust concentrations in air if small particles are formed during processing or handling.**

**Precautions:** Avoid breathing dust and wear appropriate protective equipment for respiratory, skin or eye exposures. Prevent dust release and accumulations to minimize hazards. Take off contaminated clothing and wash before reuse. Keep dust away from ignition sources such as heat, sparks, and flame.

**First Aid:** If on skin wash with plenty of mild soap and water. If in eyes, rinse cautiously for several minutes. Remove contact lenses if present and easy to do so. If experiencing respiratory symptoms, remove to fresh air. Contact a qualified medical professional for serious or persistent skin, eye or respiratory symptoms.

**Weyerhaeuser**

**33663 Weyerhaeuser Way South**

**Federal Way, WA 98001**

**1-800-525-5440**



Weyerhaeuser